Solid-state Batteries

LF51206AS / LF51206ES

Product Appearance

Product Size



Net Weight: 89.5±0.5kg

Packaging Size

Gross Weight: 116.7±0.5kg

Features

- A grade brand new solid-state cells
- > 5000 cycles @80% DOD(25°C, 0.5C)
- Over charge, over discharge, over temperature, low temperature, over current and short circuit protection
- Compatible with most inverters on the market
- Cell balance function
- Metal Case, excellent heat dissipation, more safety
- Certificate: UN38.3, MSDS, IEC62619, RoHS
- Max 8 battery packs can be connected in parallel

Electrical Characteristics

Model	LF51206AS	LF51206ES
Electrical Parameter		
Battery Type	Solid-state	
Nominal Voltage (V)	51.2	
Nominal Capacity (AH)	206	
Energy (WH)	10547	
Pack Mode	16S1P	
Charge Cut-off Voltage (V)	57.6	
Discharge Cut-off Voltage (V)	41.6	
Max.Charge Current (A)	200	
Max.Discharge Current (A)	200	
Recommend Discharge Current (A)	100	
Recommend Discharge Depth (%)	80	
Cycle Life	> 5000 cycles (25°C, 0.5C) 80% DOD	
Function	Aerosol Optional: Bluetooth/WIFI/Heating/Breaker	
Communication	RS485 CAN	
Display	LCD	LED
Mounting	Floor-mounted & Top wiring	
Environmental Parameter		
Charge&Discharge Temperature (°C)	Charge: 0°C~+50°C / Discharge: -20°C~+50°C	
Optimal Storage Temperature (°C)	5°C ~ +35°C	
Relative Humidity	40%~80%	
Ingress Protection	IP65	
Mechanical Parameter		
Terminal	M8	
Dimensions (W×H×D) (mm)	550×915×160	
Weight (Kg)	89.5±0.5	
Certification	UN38.3, MSDS, EC62619, RoHS	

Performance Characteristics

Different Rate Discharge Curve@25°C



Different Temperature Discharge Curve@0. 5C



State of Charge Curve@0.5C 25°C



Charging Characteristics @0.5C 25°C



Different DOD Discharge Cycle Life Curve@0.5C 25°C



Different Temperature Self Discharge Curve



BEIJING EPSOLAR TECHNOLOGY CO., LTD.
+86-10-82894112
HUIZHOU EPEVER TECHNOLOGY CO., LTD.
+86-752-3889706
BEIJING EPSOLAR TECHNOLOGY CO., LTD. SHENZHEN BRANCH
+86-755-89236750